



**CUT D HIGH STRENGTH NYLON / NITRILE SANDY FINISH GLOVE**

A dexterous high cut resistance glove, glass and steel fibre free with excellent grip properties in all conditions.

**FEATURES**

- › Cut resistance: Level D (EN 388:2016)
- › A flexible and comfortable glove offering great dexterity
- › Glass and steel fibre free reduce risks of irritation
- › Nitrile sandy finish on palm provides a secure grip in light oily, greasy and dry conditions
- › Flexible, close-fitting design for a comfortable wearing experience
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



**SUITABLE FOR**

**Typical Industries**

- Aerospace
- Engineering
- Automotive
- Logistics
- Construction
- Manufacturing

**Suitable Applications**

- Assembly
- Handling sharp and oily parts
- Maintenance
- Injection molding
- Machining
- Bodyworks

**CERTIFICATION**



See overleaf for explanation



**PRODUCT INFORMATION**

<b>MATERIALS</b>	LINER:	13 gauge high strenght nylon
	COATING:	Nitrile sandy finish
<b>COLOUR</b>	Grey/Black	
<b>LENGTH (mm)</b>	250 (Size Dependent)	
<b>CUFF STYLE</b>	Elasticated knit wrist	

**ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS	BMG00758FB	10 pairs per bag 120 pairs per case
7/S	BMG00758FD	
8/M	BMG00758FF	
9/L	BMG00758FH	
10/XL	BMG00758FJ	
11/XXL	BMG00758FL	


**RECOMMENDATIONS FOR USE**

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

**CERTIFICATION LEGENDS**



MECHANICAL HAZARDS EN 388:2016  
PERFORMANCE LEVELS\*



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

**EUROPE**

[www.globus.co.uk](http://www.globus.co.uk)

**E:** sales@globus.co.uk  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

**MIDDLE EAST AND AFRICA**

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** gcc@globusgroup.com  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM  
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | BMK-DATA-BMG758\_0720\_1